




The World's First **Battery-less Off-Grid** Solar Inverter for Air Conditioners

CyboInverter



- For Inverter-Air-Conditioners (IAC), Requiring no Batteries
- Supports 9000 to 24000 Btu IAC
- Pure Sinewave AC Output
- Four DC Input Channels
- MPPT for Each Solar Panel
- Over Discharge Protection for 48V Lead-Acid Batteries
- Solar or Battery Auto-Detection
- High Efficiency and Long Life

One Master (CI-Mini-1000N1x) & Slave (CI-Mini-1000N2x) off-grid CyboInverter can daisy-chain, and produce up to 2500W, 120V, 60Hz AC to run Inverter-Air-Conditioners (IAC).




Product: Off-Grid CyboInverter Twin Pack for A/C Units (8 Input Channels)

Part No: CI-Mini-1000N1x / N2x, Daisy-Chained Off-Grid Model, 120V, 60Hz AC

Never connect the Off-Grid CyboInverter to the AC grid. Doing so will damage the unit and void the warranty. Check voltage and current specs of A/C Unit before attaching.



Technical Data of CI-Mini-1000N1x and N2x (Rev 6.0 – July 2019)

DC Input (per Channel)	60 / 72 Cell Panel	Battery*
Supported Input Power	250W – 380W	48V, 50AH – 300AH
Operating Input DC Voltage Range	15V – 58V	47V – 58V
Peak Power Performance Range	30V – 58V	48V – 58V
Maximum Input DC Voltage / Current	58V / 10.5A	58V / 10.5A
Maximum Input Power	330W	330W
Minimum Starting Voltage	20V	47V
AC Output (per Inverter)	Data	
Rated Output Power / Peak Output Power	960W / 1250W	
Startup Surge Power for 12 Seconds	1500W (Max Surge DC Power = 400W per Channel)	
Nominal Output Current (RMS)	8A (RMS – Root Mean Square)	
Nominal Output Voltage / Range	120V (90V – 132V, Single-Phase)	
Nominal Frequency / Range	60Hz (59.5Hz – 60.5Hz)	
Power Factor	>0.95	
Efficiency	Data	
Peak Efficiency / MPPT Tracking	96% (99%)	
Mechanical Data	SI	U.S.
Ambient Temperature Range	-40°C to +65°C	-40°F to +149°F
Internal Operating Temperature Range	-40°C to +88°C	-40°F to +190°F
Dimensions w/o mounting bracket (L x H x W)	32cm x 24cm x 5.8cm	12.5” x 9.5” x 2.3”
Weight	6.5 kg	14.25 lbs
Cooling / Enclosure	Natural Convection, No Fan / Potted	
DC Wire / AC Wire	1-2 Feet DC Wires / 12 Feet AC Wires (THHN), Copper	
Features and Compliance	Data	
Safety and EMC Compliance	UL1741 and IEEE1547 (E113426), CSA 107.1, FCC Part 15 Class A	
Rapid Shutdown	Complies with NEC 2014/2017 690.12.	
DC Ground Fault Detector Interrupter (GFDI)	Built-In	
Standard Warranty	3 Years (Extended Warranty Available)	
Enclosure Environmental Rating / Safety	Outdoor – NEMA 6 / Transformer Isolated Circuits	
Built-in Battery Over Discharge Protection	Low Voltage Disconnect (LVD) on Battery Channels.	

* Supports 48V Lead-Acid Battery or 20V-55V Lithium Battery Packs. No batteries are required to run Inverter-Air-Conditioners (IAC) during the day when there is sufficient sunlight.